

Dr D Y Patil Pratishthan's

**Dr. D.Y. Patil Institute of Engineering, Management and Research,
Akurdi, Pune**

**Academic
Year:2021-22**

Department : FE

Term – I

Name of Course : ENGINEERING PHYSICS (107002)

Name of Course : ENGINEERING PHYSICS (107002)

Examination Pattern : INSEM 30 m ENDSEM 70M

Class : FE ABCD

Division : A&C

Unit No. : 5

Faculty Name : DR VANDANA B PATIL


Dr D Y Patil Pratishthan's
Dr. D.Y. Patil Institute of Engineering, Management and
Research, Akurdi, Pune

**Academic
Year:2021-22**

Department : FE

Term – I

Name of Course :ENGINEERING PHYSICS



**Academic Year:
2021-22**

Department :FE

Term – I

Name of Course : ENGINEERING PHYSICS

Magnetism

- ❖ **Magnetism:** Study of Effect of magnet and its effects
- ❖ **Origin of magnet:** Every rotating / spinning charged particle develops magnetic effect.
- ❖ **Origin of Magnetism.** **Magnetism** originates from the spin and orbital magnetic moment of an electron. The orbital motion of an electron around the nucleus is analogous to the current in a loop of wire.

**Academic Year:
2021-22**

Department : FE

Term – I

Name of Course :ENGINEERING PHYSICS

Some terms in Magnetism

- ❖ **Magnetic field strength: (H)** – The magnitude of the force experienced by unit North pole at any point in the field is called as The Strength of the Magnetic Field at that point
- ❖ Units MKS N/Am or W/m²
- ❖ CGS: Gauss or oersted
- ❖ **Magnetic Induction or Flux Density (B)**: It is the number of hypothetical induction lines passing normally through unit area. **Unit: Tesla (T) or weber / m²**

**Academic Year:
2021-22**

Department : FE

Term – I

Name of Course :ENGINEERING PHYSICS

Intensity of magnetization I

- ❖ It measures the degree of magnetisation of a magnetised specimen and is defined as magnetic moment per unit volume $I =$ **(Magnetic moment (M) / Volume**
- ❖ Magnetic Susceptibility $\chi = I / H$
- ❖ Magnetic permeability $\mu = B / H$
- ❖ For free space it is $4\pi \times 10^{-7}$ Henry / m

**Academic Year:
2021-22**

Department : FIRST YEAR ENGINEERING

Term – I

Name of Course : ENGINEERING PHYSICS

Types of magnetic material

Diamagnetic materials

Properties

- No permanent dipole or magnetic moment is present.
- The external magnetic field produces induced magnetic moment.
- Induced magnetic moment is always in opposite direction of the applied magnetic field.
- So magnetic induction in the specimen decreases.
- Magnetic susceptibility is small and negative.
- Repels magnetic lines of force.

**Academic Year:
2021-22**

Department : FIRST YEAR ENGINEERING

Term – I

Name of Course : ENGINEERING PHYSICS

Types of magnetic material

Paramagnetic materials

Properties

- Possess permanent dipoles.
- In the absence of external mag. Field all dipoles are randomly oriented so net magnetic moment is zero.
- In presence of magnetic field the material gets feebly magnetized.
- i.e. the material allows magnetic lines of force to pass through it.
- The orientation of magnetic dipoles depends on temperature and applied field.
- Susceptibility is small and positive.

**Dr. D.Y. Patil Institute of Engineering, Management and Research,
Akurdi, Pune**

**Academic Year:
2021-22**

Department : FIRST YEAR ENGINEERING

Term – I

Name of Course : ENGINEERING PHYSICS

Types of magnetic material

Properties

Susceptibility is independent of applied mag. field & depends on temperature

C is Curie constant


Spin alignment is random.

The magnetic dipoles do not interact.

These materials are used in lasers.

Paramagnetic property of oxygen is used in NMR technique for medical diagnose.

Examples: alkali metals (Li, Na, K, Rb), transition metals, Al, Pt, Mn, Cr etc.



**Dr. D.Y. Patil Institute of Engineering, Management and Research,
Akurdi, Pune**

**Academic Year:
2021-22**

Department : FIRST YEAR ENGINEERING

Term – I


Name of Course : ENGINEERING PHYSICS

Ferromagnetic materials

Types of magnetic material

Properties

- Possess net magnetic moment
- Possess spontaneous magnetization.
- Material shows magnetic properties even in the absence of external magnetic field.
- Spontaneous magnetization is because of interaction between dipoles called EXCHANGE COUPLING.
- When placed in external mag. field it strongly attracts magnetic lines of force.
- All spins are aligned parallel & in same direction



**Academic Year:
2021-22**

Department : FIRST YEAR ENGINEERING


Term – I

Name of Course : ENGINEERING PHYSICS

Types of magnetic material

Antiferromagnetic Material Properties

- The spin alignment is in antiparallel manner.
- So net magnetic moment is zero.
- Susceptibility is small and positive.
- Initially susceptibility increases with increase in temperature and beyond Neel temperature the susceptibility decreases with temperature.
- At Neel temperature susceptibility is maximum.
- Examples: FeO , MnO , Cr_2O_3 and salts of transition elements.



**Academic Year:
2021-22**

Department : FIRST YEAR ENGINEERING

Term – I

Name of Course : ENGINEERING PHYSICS

Types of magnetic material

Ferrimagnetic Materials

Properties

Special type of antiferromagnetic material.


The spin alignment is antiparallel but different magnitude.

So they possess net magnetic moment.

Also called ferrites.

Susceptibility is very large and positive.

Examples: ferrous ferrite, nickle ferrite



**Academic Year:
2021-22**

Department : FIRST YEAR ENGINEERING

Term – I

Name of Course : ENGINEERING PHYSICS

Types of magnetic material

Diamagnetic materials

Properties


- No permanent dipole or magnetic moment is present.
- The external magnetic field produces induced magnetic moment.
- Induced magnetic moment is always in opposite direction of the applied magnetic field.
- So magnetic induction in the specimen decreases.
- Magnetic susceptibility is small and negative.
- Repels magnetic lines of force.

Magnetic Domains

Two ways for aligning of magnetic domains:

1. Growth of favorably oriented domains (initially)
2. Rotation of domains (finally)


Magnetic domains



- Applying very strong fields can saturate magnetization by creating single domain

Hysteresis Curve

- Means lagging or retarding of an effect behind the cause of the effect.
- Here effect is B & cause of the effect is H .
- Also called B H curve.
- Hysteresis in magnetic materials means lagging of magnetic induction (B) or magnetization (M) behind the magnetizing field (H).




Remanence: a measure of the remaining magnetization when the driving field is dropped to zero.



Coercivity: a measure of the reverse field needed to drive the magnetization to zero after being saturated.




Saturation



$$\text{remanent magnetization} = M_0$$

$$\text{coercivity} = H_c$$



Desirable for permanent magnets and magnetic recording and memory devices.

The area of the hysteresis loop is related to the amount of energy dissipation upon reversal of the field.

Desirable for transformer and motor cores to minimize the energy dissipation with the alternating fields associated with AC electrical applications.

“hard” ferromagnetic material has a large M_0 and large H_c .

“soft” ferromagnetic material has both a small M_0 and H_c .

